

Direct Interactive Programs

Good:

```
(define (num-read prompt)
  (begin
    (printf "~a\n" prompt)
    (read)))
```

```
(define (h)
  (+ (num-read "First number")
     (num-read "Second number")))
```

Interactive Web Programs

Adequate:

```
(define (web-read/k prompt cont)
  (local [(define key (remember cont))]
    `(,prompt
      "To continue, call resume/k with" ,key "and value")))
```

```
(define (resume/k key val)
  (local [(define cont (lookup key))]
    (cont val)))
```

```
(define (do-h cont)
  (web-read/k "First"
    (lambda (v1)
      (web-read/k "Second"
        (lambda (v2)
          (cont (+ v1 v2))))))))
```

```
(define (h)
  (do-h identity))
```

Interactive Web Programs

Better:

```
(define (web-read prompt)
  ...
  (local [(define key (remember cont))])
  `(,prompt
    "To continue, call resume with" ,key "and value"))
  ...)
```

```
(define (resume key val)
  (local [(define cont (lookup key))])
  (cont val)))
```

```
(define (h)
  (+ (web-read "First")
     (web-read "Second")))
```

If we can implement this `web-read` somehow...

Implicit Continuations

With

```
(define (h)
  (+ (web-read "First")
     (web-read "Second")))
(h)
```

The implicit **continuation** of the first call to `web-read` is

```
(lambda (•)
  (+ •
     (web-read "Second")))
```

Implicit Continuations

With

```
(define (h)
  (+ (web-read "First")
     (web-read "Second")))
(h)
```

If the first `web-read` call produces `7`, then the continuation of the second `web-read` call is

```
(lambda (•)
  (+ 7
     •))
```

Implicit Continuations

With

```
(define (do-g total)
  (do-g (+ (web-read (format "Total: ~a" total))
          total)))
(do-g 0)
```

The continuation of the first call to `web-read` is

```
(lambda (•)
  (do-g (+ •
          0)))
```

Implicit Continuations

With

```
(define (do-g total)
  (do-g (+ (web-read (format "Total: ~a" total))
          total)))
(do-g 0)
```

If the first `web-read` call produces `7`, then the continuation of the second `web-read` call is

```
(lambda (•)
  (do-g (+ •
          7)))
```

Implicit Continuations

With

```
(define (do-g total)
  (do-g (+ (web-read (format "Total: ~a" total))
          total)))
(do-g 0)
```

If the second `web-read` call produces `8`, then the continuation of the second `web-read` call is

```
(lambda (•)
  (do-g (+ •
          15)))
```

etc.

Implementing web-read

We need an operation to convert the current *implicit* continuation into an *explicit* continuation:

```
(define (web-read prompt)
  ...
  (get-current-continuation)
  ...
  (local [(define key (remember cont))]
    ` (,prompt
      "To continue, call resume with"
      ,key "and value"))
  ...)
```

This is not quite right, because the continuation of `(get-current-continuation)` is some context that wants a continuation, not the continuation of the `web-read` call...

Implementing web-read

`let/cc` locally binds a name to the “surrounding” continuation, and evaluates its body to produce a result:

```
(define (web-read prompt)
  (let/cc cont
    (local [(define key (remember cont))]
      `(,prompt
        "To continue, call resume with"
        ,key "and value"))))
```

Closer, but we need to escape instead of returning...

Implementing web-read

For now, use `error` to escape:

```
(define (web-read prompt)
  (let/cc cont
    (local [(define key (remember cont))]
      (error 'web-read
             "~a; to continue, call resume with ~a and value"
             prompt key))))
```

Reusing Direct-Style Web Pages

No more CPS, so re-using **h** for **i** is easy:

```
(define (web-pause prompt)
  (let/cc cont
    (local [(define key (remember cont))]
      (error 'web-pause
              "~a; to continue, call p-resume with ~a"
              prompt key))))
```

```
(define (p-resume key)
  (local [(define cont (lookup key))]
    (cont (void))))
```

```
(define (i)
  (web-pause (h))
  (h))
```

Reusing Direct-Style Web Pages

No CPS also means that we can use functions like `map`:

```
(define (web-read-each prompts)
  (map web-read prompts))

(define (m)
  (apply format "my ~a saw a ~a rock"
    (web-read-each '("noun" "adjective"))))
```

Continuations in web-read-all

```
(define (web-read-each prompts)
  (map web-read prompts))

(define (m)
  (apply format
    "my ~a saw a ~a rock"
    (web-read-each '("noun" "adjective"))))

(define (map f l)
  (cond
    [(empty? l) empty]
    [else (cons (f (first l))
                 (map f
                     (rest l)))])])
```

Evaluation:

```
(m)
⇒ (apply format "my ~a saw a ~a rock"
      (web-read-each '("noun" "adjective")))
```

Continuations in web-read-all

```
(define (web-read-each prompts)
  (map web-read prompts))

(define (m)
  (apply format
    "my ~a saw a ~a rock"
    (web-read-each '("noun" "adjective"))))

(define (map f l)
  (cond
    [(empty? l) empty]
    [else (cons (f (first l))
                 (map f
                     (rest l)))])])
```

Evaluation:

```
(apply format "my ~a saw a ~a rock"
  (web-read-each '("noun" "adjective")))

⇒ (apply format "my ~a saw a ~a rock"
  (map web-read '("noun" "adjective")))
```

Continuations in web-read-all

```
(define (web-read-each prompts)
  (map web-read prompts))
```

```
(define (m)
  (apply format
    "my ~a saw a ~a rock"
    (web-read-each '("noun" "adjective"))))
```

```
(define (map f l)
  (cond
    [(empty? l) empty]
    [else (cons (f (first l))
                 (map f
                      (rest l)))]))
```

Evaluation:

```
(apply format "my ~a saw a ~a rock"
  (map web-read '("noun" "adjective")))
```

```
⇒ (apply format "my ~a saw a ~a rock"
  (cond
    [(empty? '("noun" "adjective")) empty]
    [else (cons (web-read (first '("noun" "adjective"))
                       (map web-read
                            (rest '("noun" "adjective"))))]))
```


Continuations in web-read-all

```
(define (web-read-each prompts)
  (map web-read prompts))

(define (m)
  (apply format
    "my ~a saw a ~a rock"
    (web-read-each '("noun" "adjective"))))

(define (map f l)
  (cond
    [(empty? l) empty]
    [else (cons (f (first l))
                 (map f
                      (rest l)))]))
```

Evaluation:

```
(apply format "my ~a saw a ~a rock"
  (cond
    [(empty? '("noun" "adjective")) empty]
    [else (cons (web-read (first '("noun" "adjective"))
                    (map web-read
                        (rest '("noun" "adjective"))))]))
```

```
⇒ (apply format "my ~a saw a ~a rock"
  (cons (web-read (first '("noun" "adjective")))
        (map web-read
            (rest '("noun" "adjective")))))
```

Continuations in web-read-all

```
(define (web-read-each prompts)
  (map web-read prompts))

(define (m)
  (apply format
    "my ~a saw a ~a rock"
    (web-read-each '("noun" "adjective"))))

(define (map f l)
  (cond
    [(empty? l) empty]
    [else (cons (f (first l))
                 (map f
                     (rest l)))]))
```

Evaluation:

```
(apply format "my ~a saw a ~a rock"
  (cons (web-read (first '("noun" "adjective")))
    (map web-read
      (rest '("noun" "adjective")))))
```

```
⇒ (apply format "my ~a saw a ~a rock"
  (cons (let/cc cont
    (local [(define key (remember cont))]
      (error ...)))
    (map web-read
      (rest '("noun" "adjective")))))
```

Continuations in web-read-all

```
(define (web-read-each prompts)
  (map web-read prompts))
```

```
(define (m)
  (apply format
    "my ~a saw a ~a rock"
    (web-read-each '("noun" "adjective"))))
```

```
(define (map f l)
  (cond
    [(empty? l) empty]
    [else (cons (f (first l))
                 (map f
                     (rest l)))]))
```

Evaluation:

```
(apply format "my ~a saw a ~a rock"
  (cons (let/cc cont
        (local [(define key (remember cont))]
          (error ...)))
    (map web-read
      (rest '("noun" "adjective")))))
```

```
⇒ (apply format "my ~a saw a ~a rock"
  (cons (local [(define key (remember
    (lambda (•)
      (apply format "my ~a saw a ~a rock"
        (cons •
          (map web-read
            (rest '("noun" "adjective"))))))))
    (error ...))
    (map web-read
      (rest '("noun" "adjective")))))
```

Escaping

How `error` escapes (roughly):

```
(define top-level (let/cc k k))
```

```
(define (error ...)  
  ; Write error message:  
  ...  
  ; Escape:  
  (top-level top-level))
```

Applying a continuation throws away the current continuation!

So `let/cc` actually creates something like

```
(lambda↑ (•) ... • ...)
```

Direct-Style Interactive Web Pages

```
; mutated, for a kind of dynamic scope:
(define current-start-k #f)

; adjust `serve' for to set `current-start-k':
(define (serve)
  ...
  (return-page (let/cc k
                 (set! current-start-k k)
                 (dispatch (cadr m)))
                in out))

(define (web-read prompt)
  (let/cc k
    (current-start-k
     (web-read/k prompt (lambda (val)
                          (k val))))))
```

Continuations for Exceptions

```
; sum-items : list-of-num-and-sym -> num-or-false
; Returns the sum if all numbers, false otherwise
(define (sum-items l)
  (cond
    [(empty? l) 0]
    [else (if (symbol? (first l))
              false
              (if (number? (sum-items (rest l)))
                  (+ (first l) (sum-items (rest l)))
                  false))]))
```

; Better:

```
(define (sum-items l)
  (let/cc esc
    (local [(define (sum-items l)
              (cond
                [(empty? l) 0]
                [else (if (symbol? (first l))
                          (esc false)
                          (+ (first l) (sum-items (rest l))))])]
      (sum-items l))))
```

Continuations for Coroutines

```
(define tasks empty)

(define (spawn! thunk)
  (set! tasks (append tasks (list thunk))))

(define (next!)
  (local [(define t (first tasks))]
    (set! tasks (rest tasks))
    (t)))

(define (swap)
  (let/cc k
    (begin (spawn! k) (next!))))

(define (loop label cnt)
  (begin (printf "~a ~a\n" label cnt)
    (swap)
    (loop label (add1 cnt))))

(spawn! (lambda () (loop "a" 0)))
(spawn! (lambda () (loop "b" 0)))
(next!)
```